

# CONFIGURING THE ADOBE<sup>®</sup> DIGITAL ENTERPRISE PLATFORM DOCUMENT SERVICES - CONNECTOR FOR MICROSOFT<sup>®</sup> SHAREPOINT<sup>®</sup> 10.0

## **Legal notices**

For legal notices, see [http://help.adobe.com/en\\_US/legalnotices/index.html](http://help.adobe.com/en_US/legalnotices/index.html).

# Contents

- Configuring the Connector for Microsoft SharePoint**
- Overview ..... 1
- Configure enterprise domain users ..... 1
- Configure SharePoint users ..... 3
- Create LC Binding user ..... 3
- Define Impersonation user ..... 3
- Configure the Connector for Microsoft SharePoint ..... 4
- Configure policy sets and policies ..... 4
- Configure the SharePoint site ..... 4
- Set up task management ..... 6
- Integrate forms ..... 7
- Configure logging ..... 7
- Configure Document Services workflows on the SharePoint site ..... 8
- Enable search on PDF documents ..... 8
- Use the ConnectorForMSSharePoint service ..... 9
- Manage ADEP Document Services features on SharePoint sites ..... 10

# Configuring the Connector for Microsoft SharePoint

## Overview

Configuring the Adobe® Digital Enterprise Platform Document Services - Connector for Microsoft® SharePoint® 10.0 involves the following tasks:

- 1 Ensure that Adobe Document Services Connector's Web Part for SharePoint is installed on the SharePoint server.
- 2 Configure Document Services user accounts.
  - [“Configure enterprise domain users”](#) on page 1.
  - [“Configure SharePoint users”](#) on page 3.
  - [“Create LC Binding user”](#) on page 3.
  - [“Define Impersonation user”](#) on page 3.
- 3 Configure the Document Services installation.
  - [“Configure the Connector for Microsoft SharePoint”](#) on page 4 (Optional).
  - [“Configure policy sets and policies”](#) on page 4.
- 4 [“Configure the SharePoint site”](#) on page 4.
- 5 [“Set up task management”](#) on page 6 (on Microsoft SharePoint Server 2010).
- 6 [“Integrate forms”](#) on page 7 (on Microsoft SharePoint Server 2010).
- 7 [“Configure logging”](#) on page 7.
- 8 [“Configure Document Services workflows on the SharePoint site”](#) on page 8 (Optional).
- 9 [“Enable search on PDF documents”](#) on page 8.
- 10 [“Use the ConnectorForMSSharePoint service”](#) on page 9.
- 11 [“Manage ADEP Document Services features on SharePoint sites”](#) on page 10.

## Configure enterprise domain users

To ensure SharePoint user accounts are recognized on the Document Server, synchronize Document Services and SharePoint user accounts to the same user directory, such as an LDAP directory. Synchronizing user accounts with the user directory allows users to access the Adobe Digital Enterprise Platform Document Services - Rights Management 10.0 features on the SharePoint site. After synchronization, assign the Services User role to the SharePoint user accounts recognized on the Document Server.

Complete the following steps to configure enterprise domain users. If you configured enterprise domain users before installing the Connector for Microsoft SharePoint, only complete Step 3.

- 1 Log in to Document Services Administration Console and click **Settings > User Management > Domain Management**.

**2** Click **New Enterprise Domain** and enter the domain ID and name.

The domain ID is the unique identifier for the domain. When using DB2 for your Document Services database, the maximum permitted length of the ID is 100 single-byte (ASCII) characters, 50 double-byte characters, or 25 four-byte characters. Similarly, when using MySQL for your Document Services database, use only single-byte (ASCII) characters for the ID. See “Adding enterprise domains” in [Adobe Digital Enterprise Platform Document Services Administration Help](#).

**3** To add a custom authentication provider, click **Add Authentication** and perform these tasks:

- In the **Authentication Provider** list, select **Custom**.
- Select **MSSharePointAuthProvider** and then click **OK**.

***Note:** If the `MSSharePointAuthProvider` service is unavailable, restart the application server. Restarting the server after installing and configuring the Connector ensures that the Document Server recognizes the `MSSharePointAuthProvider` service as a custom authorization provider.*

**4** To add an LDAP authentication provider, click **Add Authentication** and perform these tasks:

- In the **Authentication Provider** list, select **LDAP**.
- Click **OK**.

**5** To add an LDAP directory, click **Add Directory** and perform the following tasks:

- In the **Profile Name** box, type a unique name, and click **Next**.
- Specify values for the Server, Port, SSL, Binding, and Populate page with options. If you select User for the Binding option, also specify values for the Name and Password fields.
- (Optional) Select **Retrieve Base DNs** to retrieve base domain names, as required.
- Click **Next**.
- Configure the user settings, and click **Next**.
- Configure group settings, and click **Next**.

For details about the settings, click **User Management Help** in the upper-right corner of the page.

**6** Click **Finish** to exit the Add Directory page and then click **OK** again.

**7** Select the created enterprise domain and click **Sync Now**. Depending on the number of users and groups in your LDAP network and speed of your connection, the synchronization process can take several minutes.

(Optional) To verify the status of the synchronization, click **Refresh**, and view the status in the **CurrentSync State** column.

**8** Navigate to **Settings > User Management > Users and Groups**.

**9** To search for users that were synchronized from LDAP and assign roles, perform the following tasks:

- Select one or more users and click **Assign Role**.
- Select one or more Document Services roles and click **OK**.
- Click **OK** to confirm the role assignment.
- Repeat for all users that you assign roles to.

For more information, click **User Management Help** in the upper-right corner of the page.

If you configure enterprise domain authorization provider using these steps, any processes invoked using the process context from Workbench uses the context of the user starting that process. See [Adobe Digital Enterprise Platform Document Services - Workbench 10.0 Help](#) for more information.

## Configure SharePoint users

On the SharePoint site, you can configure two types of SharePoint users:

- If you do not plan to implement Rights Management features or allow users to start Document Services processes, the user can be a local user or a user added to the user directory (Active Directory or LDAP).
- To implement Rights Management features or allow users to start Document Services processes, ensure that the user belongs to a user directory (Active Directory or LDAP) that is synchronized with Document Services. Additionally, grant the user the Services User role.

## Create LC Binding user

The SharePoint site uses the LC Binding user credentials to connect to the specified Document Server. After the connection is established, various settings, such as PDF generation and Reader Extensions, are retrieved from the Document Server and are available on the SharePoint server.

The LC Binding User is a local or enterprise user who is assigned the Services User role on the Document Server. While configuring the SharePoint site, enter the LC Binding user credentials in the user name and password fields. See [“Configure the SharePoint site”](#) on page 4 for detailed instructions.

## Define Impersonation user

### Impersonation control permission

When a SharePoint user invokes a Document Services process or Rights Management action, the SharePoint server sends a request to the Document Server. At this time, the Impersonation user credentials are used to log on to the Document Server. After logon, the Document Server verifies the identity of the SharePoint user invoking the process or action. If the SharePoint user has the required privileges, the process is executed or the policy is applied for the currently logged-in SharePoint user.

To allow SharePoint users to invoke Document Services processes and use Rights Management features, configure an Impersonation user. Enter the impersonation user details when configuring Connector for Microsoft SharePoint using the Adobe Digital Enterprise Platform Document Services - Administration Console.

### Grant Impersonation permissions

- 1 In the Administration Console, create a user account to which to assign the Identity Impersonation Control permission.  
This can be a user account synchronized with the user directory.
- 2 Create a role with the Identity Impersonation Control permission and assign this role to the created user account.  
These permissions provide the required credentials to the SharePoint Connector component deployed on the Document Server.
- 3 Navigate to **Services > Applications and Services > Service Management**.
- 4 From the **Category** list, select **Connector for MSSharePoint**.
- 5 On the Service Management page, click **MSSharePointConfigService**.

- 6 On the Configure MSSharedPointConfigService page, add the user name and password of the created user account.
- 7 Click **Save**.

## Configure the Connector for Microsoft SharePoint

If you did not configure the Connector for Microsoft SharePoint using the Configuration Manager during the installation and configuration process, configure it using the Administration Console.

- 1 Log in to Administration Console.
- 2 Navigate to **Services > Connector for Microsoft SharePoint**.
- 3 Enter the following on the SharePoint Connector Properties page.
  - **Host Name:** Enter the host name of the SharePoint server in the format *[host]:[port]*. The port number must be of the web application on the SharePoint server.
  - **User Name and Password:** Specify the user account that would be used to connect to the SharePoint server. To allow SharePoint users to access Rights Management features or invoke Document Services processes, specify the Impersonation User details. See “[Define Impersonation user](#)” on page 3.
  - **Domain Name:** Enter the domain in which the SharePoint server is present.

## Configure policy sets and policies

To use Rights Management to secure files available on the SharePoint site, you must:

- Create policy set and policies
- Add the Active Directory users to the policy set and policies

The policy set and policies (in the policy set) determine the user permissions for documents to which the policies are applied. See [Rights Management Help](#) for more information about policies and policy sets.

## Configure the SharePoint site

Configure the Document Server settings on the SharePoint site to enable SharePoint users to invoke Document Services processes from the SharePoint site.

- 1 Log in to the SharePoint site with the user name and password.
- 2 On the Sites page, click **Site Actions > Site Settings**.
- 3 On the Site Settings page, under Adobe Document Services, click **Document Services Settings**.
- 4 Enter the server parameters:
  - **Host Name and Port Number** Enter the host name and the port of the machine that hosts Document Server.
  - **User Name and Password** Enter the user name and password of a user that starts the feature from the SharePoint site. On the server, this user account must be configured with the Services User role. See “[Create LC Binding user](#)” on page 3 for information about the type of user account that you must enter. See [Adobe Digital Enterprise Platform Document Services Administration Help](#) for more information about configuring services and user accounts on Document Services.

- 5 Select Enable HTTPS Connection to connect securely to the Document Server.

*Note: Document Server should also be running in secure mode (HTTPS). Also, default secure port is normally different from the http port, so make sure to change the port as done in step 4 accordingly.*

- 6 Enter the PDF generation settings.

See “[PDF generation settings](#)” on page 5.

- 7 Specify Reader Extension settings.

See “[Reader Extension settings](#)” on page 5.

- 8 Enter Rights Management settings.

See “[Rights Management settings](#)” on page 6.

- 9 Click **Apply**.

## PDF generation settings

To ensure that users can invoke the Convert to Adobe PDF operation, in addition to specifying the following settings, ensure that PDF Generator is available on the Document Server. See PDF Generator information in [Administration Help](#).

- 1 Perform one of the following:

- Select **Use Custom Settings** to manually configure the settings.
- Select **Upload Settings File** to use a PDF settings file (.JOBOPTIONS file) to configure PDF settings. If you choose this option, all PDF configuration options are disabled.

- 2 If you selected the Use Custom Settings option, specify values for the following fields:

- **File Type Settings** Select the settings to apply to the generated PDF files.
- **Adobe PDF Settings** Select the output settings to apply to the generated PDF files.
- **Security Settings** Specify the security settings for the generated PDF files.
- **Time Out** Enter the maximum time in which to complete the conversion.
- **XMP Document** Browse and select the file containing metadata information to apply to the generated PDF file.
- **Settings Document** Browse and select the document containing settings to apply while generating the PDF file.

## Reader Extension settings

Reader Extensions must be available on the Document Server in order for users to apply usage rights on PDF documents. In addition, specify the following. See Reader Extension information in [Administration Help](#).

- **Credential Alias** Select the credential alias to use to grant usage rights.
- **Apply Usage Rights Option** Specify the run-time options to use to apply usage rights to the PDF file. To apply usage rights on PDF documents, at least one of the options must be selected

Option	Description
Basic Form Fill In	<p>Allow users to fill in and submit the completed form.</p> <p><b>Import and Export Form Data</b> Allows users to import and export form data from Adobe PDF forms.</p> <p><b>Submit Outside Web Browser</b> Allows users to submit filled-in forms using Adobe Reader.</p> <p><b>Database and Web Service Connectivity</b> Allows the PDF document to be used as an online form.</p> <p><b>Add, Delete, and Change Form Fields</b> Permits existing filled-in form fields to be edited in the PDF document.</p> <p><b>Create Pages From Templates</b> Allows users to create pages from form templates in Adobe PDF documents.</p>
2D Barcode Decoding	Enables two-dimensional barcode decoding for the PDF document.
Digital Signatures	Allows digital signatures to be added to the PDF document.
Commenting	Enables offline commenting for the PDF document.
Embedded File Attachments	Allows embedded attachments to the PDF document.
Draft Level	Allows the user to save the PDF document as a draft or final copy.
Reader Message	Represents the text displayed within Adobe Reader to inform users that the PDF document contains usage rights.

- **Select Default Protocol for BLOB** Select the encoding protocol that SharePoint site uses to exchange binary files between the SharePoint repository and the Document Server. Default is Base64 encoding.

## Rights Management settings

Rights Management must be available on Document Server in order for users to apply policy settings on documents. In addition, specify the following. See [Administration Help](#).

- **Policy Set Name:** Specify the policy set to use to secure the document. The policy sets are defined in Administration Console
- **Policy Name:** Enter the name of the policy to use to secure the document

Rights Management supports the following file types:

- Adobe PDF documents (.PDF)
- Microsoft Office 2003, 2007, and 2010 documents (.DOC, .XLS, .PPT, .DOCX, .XLSX, .PPTX)

## Set up task management

On SharePoint Server 2010, configure the user and group task lists to allow end-users access to the Document Services user and group task lists.

- 1 On the home page of your site, click **Lists**.
- 2 Click **Create**.

- 3 In **Custom Lists**, perform one of the following:
  - Select Document Services User Tasks to configure a user task list.
  - Select Document Services Group Tasks to configure a group list.
- 4 Specify the list name.
- 5 Click **Create**.

## Integrate forms

On SharePoint Server 2010, set up Document Services XDP forms as SharePoint lists to make them available to SharePoint end users.

- 1 Log in to the SharePoint site.
- 2 On the home page of your site, click **Site Actions > Site Settings**.
- 3 On the Site Settings page, under ADEP Document Services, click **Adobe Forms Library**.
- 4 On the AdobeFormsLibrary page, click the **Items** tab.
- 5 On the Items ribbon, Select **New Item > New Item**.

The Adobe Form Library page is displayed. The fields on this page are populated based on the data fetched from the Document Server. Before you configure an XDP form on the SharePoint server, ensure that the required form is configured on the Document Server. You can choose to use the provided processes that are available from the default LCA (adobe-formintegrationformssharepoint.lca) or create new processes in Document Services.

The following default processes are available:

- SharepointFormIntegrationApp/Processes/RenderAndSubmitProcess for rendering and submitting forms
- SharepointFormIntegrationApp/Processes/RenderProcess for rendering or viewing of form data along with forms
- SharepointFormIntegrationApp/Processes/RenderAndEdit for editing existing form data

- 6 Enter the list details and click **Create**.
- 7 Set permissions for the list.

## Configure logging

Specify the logging settings for SharePoint Server 2007 or 2010.

- 1 Log in to the SharePoint site.
- 2 On the home page of your site, click **Site Actions > Site Settings**.
- 3 On the Site Settings page, under ADEP Document Services, click **Logging Settings**.
- 4 On the Logging Settings page, specify the log level for the site.

***Note:** The log level applies to SharePoint Server 2007 and 2010. The log level for all sites on the SharePoint server is determined based on the most-recent log level applied by the site administrator for a site. For example, if a site administrator sets the log level to DEBUG for a site and thereafter sets the log level to INFO for another site, the log level for all sites is set to INFO.*

- 5 For SharePoint Server 2010, specify the logging type.
  - Enable ULS Logging is selected by default and logs messages to the Unified Logging System.
  - Enable Windows Event Logging allows you to log events. It is recommended you select this option if ULS logging is disabled on the SharePoint server.

*Note:* To configure event-based logging, create an event category in the registry. For detailed instructions on creating an event category, see the Microsoft Support website article at <http://support.microsoft.com/default.aspx?scid=kb;en-us;329291>. When creating the key, specify Document ServicesSharePointConnector as the key name.
- 6 Click **Apply**.

## Configure Document Services workflows on the SharePoint site

To automatically initiate Document Services processes from within SharePoint, configure the Document Services workflows on the SharePoint site.

- 1 On the home page of your site, click **Shared Documents**.
- 2 Perform one of the following steps:
  - For SharePoint Server 2007, on the Shared Documents page, select **Settings > Document Library Settings**.
  - For SharePoint Server 2010, switch to the Library tab and select **Library Settings**.
- 3 Under Permissions and Management, click **Workflow settings**.
- 4 Under Workflows, click **Add a workflow**.
- 5 In the **Select a workflow template** list, select **ADEP Document Services Workflow**.
- 6 Enter the required details and click **Next**. If you create a task or history list, the name of the list is prefixed with the specified workflow name.
- 7 On the Invoke ADEP Document Services Action page, do the following:
  - Select the Document Services action that the SharePoint workflow will invoke. If you select Invoke ADEP Document Services Process, select the Document Services process to be invoked. The list contains only Document Services processes that accept a document as an input parameter.
  - For all Document Services actions selected, specify the location where the resulting documents must be saved. By default, the resulting documents are saved in the same location as the source. To select a custom location as the destination, select Custom Location and navigate to the required folder in the CurrentSite navigation tree.
- 8 Click **Submit**.

## Enable search on PDF documents

After you install and configure Connector for Microsoft SharePoint, enable search on PDF documents. By default, SharePoint Server does not crawl PDF documents.

## Add PDF file type

- 1 Log in to SharePoint Server's Central Administration Console.
- 2 On the left pane, click **General Application Settings**.
- 3 Under Search, click **Farm Search Administration**.
- 4 Under Search Service Applications, click **Search Service Application**.
- 5 On the left panel, under Crawling, click **File Types**.
- 6 Click **New File Type**, and in the File Name Extension, type pdf and click **OK**.

## Restart SharePoint services

- ❖ Restart the following services on the machine:
  - SharePoint Foundation Search
  - SharePoint Server Search
  - IIS Admin Service

*Note: You may be required to restart the machine after restarting these services.*

## Run a Full Crawl on SharePoint Server

- 1 Log in to SharePoint Server's Central Administration Console.
- 2 On the left pane, click **General Application Settings**.
- 3 Under Search, click **Farm Search Administration**.
- 4 Under Search Service Applications, click **Search Service Application**.
- 5 On the left panel, click **Content Sources**.
- 6 Click **Local SharePoint Sites** list, and select **Start Full Crawl**.

A full crawl can take several minutes. After the Full Crawl is completed, PDF documents appear in the search results.

## Use the ConnectorForMSSharePoint service

The ConnectorForMSSharePoint service can be used to connect Document Services processes to SharePoint web applications configured with authentication type as Windows.

*Note: Forms authentication is not supported.*

When using the Windows authentication type for domain users, complete the following:

- Specify the user name in the *domain\user* format in all SharePoint service operations.
- Enable Basic Authentication in the Central Administration console of the SharePoint server (only for SharePoint 2010). See SharePoint Help for more information.

*Note: SharePoint supports both Basic and NTLM authentication. However, NTLM is supported only for users on Windows. If you have domain users, enable Basic authentication or both Basic Authentication and NTLM on the SharePoint site.*

## Manage ADEP Document Services features on SharePoint sites

By default, when you configure the SharePoint server with the ADEP Document Services features, all features available on the Document Server are available for configuration on *all* sites on the SharePoint server. This is because you installed the ADEP Document Services SharePoint Connector web part on the SharePoint server that hosts all the sites. For example, if the Document Server instance has Rights Management, PDF Generator, and Reader Extensions available on the Document Server, all sites on the SharePoint server will have these features available. You can manage the Document Services features in the following ways:

- Enable or disable all Document Services features or workflows on a site
- Selectively disable Document Services features on all sites
- Uninstall the ADEP Document Services SharePoint Connector web part from the SharePoint server

*Note: Making changes to SharePoint Server affects all sites that are on the server. Exercise caution when you enable or disable ADEP Document Services features and workflows or uninstalling the SharePoint Connector web part.*

### Disable or enable ADEP features or workflows

You can disable all ADEP features on any site on the SharePoint server. Keep in mind that this step removes all the ADEP Document Services features from the specified site. If the specified site has any child sites, only the parent site will have the ADEP features deactivated. For example, if you deactivate the ADEP features on the site `http://mysite:80`, its child site `http://mysite:80/subsite` is not affected. Similarly, other sites on the same SharePoint server are not affected.

On the other hand, disabling or enabling workflow works only for a site collection and not for a site or subsite. That is, enable of disable command for workflow will work with site URL is `http://mysite:80/` but not when site URL is `http://mysite:80/site`.

### Disable ADEP features and workflows

1 Open a command prompt, and navigate to the `%TEMPLATEDIR%\FEATURES` folder on the Windows machine that hosts SharePoint Server. The default location of the TEMPLATE directory is `C:\Program Files\Common Files\Microsoft Shared\Web Server Extensions\14\`.

2 Enter the following commands:

- To deactivate ADEP Document Services Connector feature with WSS:

```
%STSADM% -o deactivatefeature -filename LiveCycle\feature.xml -url %SITEURL% -force
```

- To deactivate ADEP Document Services Workflow feature with WSS:

```
%STSADM% -o deactivatefeature -name LiveCycle/Workflow -url %SITEURL% -force
```

In these commands, replace the variables with relevant values. See *Appendix- Configuring Connector for Microsoft SharePoint on the SharePoint server* in the installation guide for ADEP Document Server for information about these parameters.

**%STSADM%** The location of the STSADM utility that you defined as part of the web part installation.

**%TEMPLATEDIR%** The TEMPLATES directory on the SharePoint server.

**%SITEURL%** The URL of the site on which you want to disable the ADEP Document Services features.

3 Restart the IIS server.

### Enable ADEP features and workflows

1 Open a command prompt, and navigate to the %TEMPLATEDIR%\FEATURES folder on the Windows machine that hosts SharePoint Server.

2 Enter the following commands:

- To activate ADEP Document Services Connector feature with WSS:

```
%STSADM% -o activatefeature -filename LiveCycle\feature.xml -url %SITEURL% -force
```

- To activate ADEP Document Services Workflow feature with WSS:

```
%STSADM% -o activatefeature -name LiveCycle/Workflow -url %SITEURL% -force
```

In these commands, replace the variables with relevant values. See *Appendix- Configuring Connector for Microsoft SharePoint on the SharePoint server* in the installation guide for ADEP Document Server for information about these parameters.

3 Restart the IIS server.

### Selectively disable ADEP features on all SharePoint sites

You can selectively disable Document Server features that are available. Keep in mind that these changes affect *all* sites on the SharePoint server. To make such changes, you remove the feature configuration defined in the %TEMPLATEDIR%\FEATURES\LiveCycle\Elements.xml file.

For example, to make only the PDF Generator feature available on SharePoint sites, you remove the definitions for Reader Extensions, Rights Management and Invoke Adobe LiveCycle Process from the Elements.xml file. These definitions are enclosed in CustomAction elements. To disable a feature, you remove or comment out the CustomAction elements related to the features. For example, to disable Rights Management features, you remove CustomAction elements that have the Id starting with LiveCycle.RightsManagement.

1 Navigate to the %TEMPLATEDIR%\FEATURES\LiveCycle folder, and make a back up copy of the Elements.xml file.

2 Open the Elements.xml file in a text editor.

3 Depending on the Document Server feature to be disabled, identify the CustomAction elements related to the Document Services feature, and delete entire elements.

Document Server feature	CustomAction element ID	Description
Reader Extensions	LiveCycle.ApplyReaderExtensions	Enables Reader Extensions on PDF documents.

<b>Document Server feature</b>	<b>CustomAction element ID</b>	<b>Description</b>
Rights Management	LiveCycle.RightsManagement.ApplyPolicy ToPdf	Rights-protect PDF documents
	LiveCycle.RightsManagement.ApplyPolicy ToDoc	Rights-protect Microsoft Word documents
	LiveCycle.RightsManagement.ApplyPolicy ToXls	Rights-protect Microsoft Excel documents
	LiveCycle.RightsManagement.ApplyPolicy ToPpt	Rights-protect Microsoft PowerPoint documents
	LiveCycle.RightsManagement.ApplyPolicy ToDocx	Rights-protect Microsoft Word documents
	LiveCycle.RightsManagement.ApplyPolicy ToXlsx	Rights-protect Microsoft Excel documents
	LiveCycle.RightsManagement.ApplyPolicy ToPptx	Rights-protect Microsoft PowerPoint documents
	LiveCycle.RightsManagement.ApplyPolicy ToDwg	Rights-protect Microsoft Excel documents
	LiveCycle.RightsManagement.ApplyPolicy ToDxf	Rights-protect AutoCAD documents
	LiveCycle.RightsManagement.ApplyPolicy ToDwf	Rights-protect AutoCAD documents

<b>Document Server feature</b>	<b>CustomAction element ID</b>	<b>Description</b>
PDF Generator	LiveCycle.GeneratePDFFromPdf	Convert a PDF created from an image to a text-based PDF if Standard OCR was used as the file type in Site Settings.
	LiveCycle.GeneratePDFFromDoc	Generate PDF from Microsoft Word documents
	LiveCycle.GeneratePDFFromPs	Generate PDF from PostScript files
	LiveCycle.GeneratePDFFromEps	Generate PDF from EPS documents
	LiveCycle.GeneratePDFFromPrn	Generate PDF from PRN files
	LiveCycle.GeneratePDFFromDocx	Generate PDF from Microsoft Word 2007 documents
	LiveCycle.GeneratePDFFromPpt	Generate PDF from Microsoft PowerPoint documents
	LiveCycle.GeneratePDFFromPptx	Generate PDF from Microsoft PowerPoint documents
	LiveCycle.GeneratePDFFromXls	Generate PDF from Microsoft Excel documents
	LiveCycle.GeneratePDFFromXlsx	Generate PDF from Microsoft Excel documents
	LiveCycle.GeneratePDFFromBmp	Generate PDF from BMP files
	LiveCycle.GeneratePDFFromGif	Generate PDF from GIF images
	LiveCycle.GeneratePDFFromJpeg	Generate PDF from JPEG images
	LiveCycle.GeneratePDFFromJpg	Generate PDF from JPG images
	LiveCycle.GeneratePDFFromTiff	Generate PDF from TIFF images
	LiveCycle.GeneratePDFFromTif	Generate PDF from TIF images
	LiveCycle.GeneratePDFFromPng	Generate PDF from PNG images
	LiveCycle.GeneratePDFFromJpf	Generate PDF from JPF images
	LiveCycle.GeneratePDFFromJpx	Generate PDF from JPX images
	LiveCycle.GeneratePDFFromJp2	Generate PDF from JPEG 2000 images
	LiveCycle.GeneratePDFFromJ2k	Generate PDF from JPEG 2000 images
	LiveCycle.GeneratePDFFromJ2c	Generate PDF from JPEG 2000 images
	LiveCycle.GeneratePDFFromJpc	Generate PDF from JPEG 2000 images
	LiveCycle.GeneratePDFFromHtm	Generate PDF from HTM documents
	LiveCycle.GeneratePDFFromHtml	Generate PDF from HTML documents
	LiveCycle.GeneratePDFFromSwf	Generate PDF from SWF files
	LiveCycle.GeneratePDFFromFlv	Generate PDF from Flash video files
LiveCycle.GeneratePDFFromTxt	Generate PDF from text files	
LiveCycle.GeneratePDFFromRtf	Generate PDF from Rich Text Format files	
LiveCycle.GeneratePDFFromMpp	Generate PDF from Microsoft Project files	

Document Server feature	CustomAction element ID	Description
Invoke ADEP Document Services process	LiveCycle.InvokeGenericLiveCycleProcess OnALL	Invoke ADEP Document Services Process
Adobe Forms Library	AdobeFormsLibrary	Set up SharePoint as the repository for forms data.  Remove the CustomAction, ListTemplate and ListInstance elements.
LiveCycle User Tasks	LiveCycleUserTasks	Lists the user tasks.  Remove the ListTemplate element.
LiveCycle Group Tasks	LiveCycleGroupTasks	Lists the group tasks.  Remove the ListTemplate element.

- 4 Save the Elements.xml file.
- 5 Restart IIS server for the changes to take effect.

## Uninstall the ADEP Document Services Connector web part

You can uninstall the web part from the SharePoint server. The uninistallation process restarts the IIS Server.

- 1 Copy the following text in a text editor and make the required changes. See *Appendix- Configuring Connector for Microsoft SharePoint on the SharePoint server* in the installation guide for ADEP Document Server for information about these parameters. You must remove any special formatting marks from the text.

```
set _my_datetime=%date% %time%
@echo on
echo Begin Uninstallation at %_my_date time%
echo "Customize <VER> <PORT> <SharepointServerNameOrIP> <SiteDirectory> <siteName> in this
install.bat file. Verify gacutil.exe path."
@echo off
@SET GACUTIL.exe="C:\Program Files\Microsoft SDKs\Windows\v6.0A\bin\gacutil.exe"
@SET TEMPLATEDIR="C:\Program Files\Common Files\Microsoft Shared\web server
extensions\<VER>\TEMPLATE"
@SET ISAPIDIR="C:\Program Files\Common Files\Microsoft Shared\web server
extensions\<VER>\ISAPI"
@SET RESOURCESDIR="C:\Program Files\Common Files\Microsoft Shared\web server
extensions\<VER>\Resources"
@SET WEBAPPPDIR="C:\Inetpub\wwwroot\wss\VirtualDirectories\<Port>"
@SET SITEURL="http://<SharepointServerNameOrIP>:<port>/<SiteDirectory>/<siteName>/"
@SET STSADM="C:\Program Files\Common Files\Microsoft Shared\web server
extensions\<VER>\bin\stsadm.exe"
REM cd $(ProjectDir)
%GACUTIL.exe% /nologo /u
"AdobeLCSharepoint,Version=1.0.0.0,PublicKeyToken=6720cbcc342f4ca4" /f
%GACUTIL.exe% /nologo /u
"AdobeLiveCycleConnector,Version=1.0.0.0,PublicKeyToken=6720cbcc342f4ca4" /f
%GACUTIL.exe% /nologo /u
"AdobeLiveCycleWorkflow,Version=1.0.0.0,PublicKeyToken=6720cbcc342f4ca4" /f
%GACUTIL.exe% /nologo /u
"AdobeLCFormsIntgr,Version=1.0.0.0,PublicKeyToken=6720cbcc342f4ca4" /f
```

```
%GACUTILEXE% /nologo /u "AdobeLCFormsIntgrListExtnWebService,Version=1.0.0.0,
PublicKeyToken=6720cbcc342f4ca4" /f
%GACUTILEXE% /nologo /u
"AdobeLCTaskManager,Version=1.0.0.0,PublicKeyToken=6720cbcc342f4ca4" /f
pushd %TEMPLATEDIR%\features
Echo Deactivating LiveCycle Connector feature with WSS
%STSADM% -o deactivatefeature -filename LiveCycle\feature.xml -url %SITEURL% -force
Echo Deactivating LiveCycle Workflow feature with WSS
%STSADM% -o deactivatefeature -name LiveCycle/Workflow -url %SITEURL% -force
Echo Uninstalling LiveCycle Connector with WSS
%STSADM% -o uninstallfeature -filename LiveCycle\feature.xml -force
Echo Uninstalling LiveCycle Workflow with WSS
%STSADM% -o uninstallfeature -name LiveCycle/Workflow -force
popd
Echo Removing source files from WSS \TEMPLATE directory
RMDIR %TEMPLATEDIR%\FEATURES\LiveCycle /S /Q
RMDIR %TEMPLATEDIR%\IMAGES\LiveCycle /S /Q
RMDIR %TEMPLATEDIR%\LAYOUTS\LiveCycle /S /Q
Echo Removing Custom Web Service files from WSS \ISAPI directory
RMDIR %ISAPIDIR%\LiveCycle /S /Q
Echo Removing Feature Resource files from WSS 12\Resources directory
Del %RESOURCESDIR%\AdobeLiveCycleConnectorCore.de-DE.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleConnectorCore.de.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleConnectorCore.en-US.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleConnectorCore.en.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleConnectorCore.fr-FR.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleConnectorCore.fr.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleConnectorCore.ja-JP.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleConnectorCore.ja.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleConnectorCore.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleFormsIntgrCore.de-DE.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleFormsIntgrCore.de.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleFormsIntgrCore.en-US.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleFormsIntgrCore.en.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleFormsIntgrCore.fr-FR.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleFormsIntgrCore.fr.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleFormsIntgrCore.ja-JP.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleFormsIntgrCore.ja.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleFormsIntgrCore.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleTaskManagerCore.de-DE.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleTaskManagerCore.de.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleTaskManagerCore.en-US.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleTaskManagerCore.en.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleTaskManagerCore.fr-FR.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleTaskManagerCore.fr.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleTaskManagerCore.ja-JP.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleTaskManagerCore.ja.resx /F /Q
Del %RESOURCESDIR%\AdobeLiveCycleTaskManagerCore.resx /F /Q
Echo Removing Resource files from %WEBAPPPDIR%\App_GlobalResources directory
Del %WEBAPPPDIR%\App_GlobalResources\AdobeLiveCycleConnector.de-DE.resx /F /Q
Del %WEBAPPPDIR%\App_GlobalResources\AdobeLiveCycleConnector.de.resx /F /Q
Del %WEBAPPPDIR%\App_GlobalResources\AdobeLiveCycleConnector.en-US.resx /F /Q
Del %WEBAPPPDIR%\App_GlobalResources\AdobeLiveCycleConnector.en.resx /F /Q
Del %WEBAPPPDIR%\App_GlobalResources\AdobeLiveCycleConnector.fr-FR.resx /F /Q
Del %WEBAPPPDIR%\App_GlobalResources\AdobeLiveCycleConnector.fr.resx /F /Q
Del %WEBAPPPDIR%\App_GlobalResources\AdobeLiveCycleConnector.ja-JP.resx /F /Q
Del %WEBAPPPDIR%\App_GlobalResources\AdobeLiveCycleConnector.ja.resx /F /Q
```

```
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleConnector.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleFormsIntgr.de-DE.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleFormsIntgr.de.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleFormsIntgr.en-US.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleFormsIntgr.en.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleFormsIntgr.fr-FR.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleFormsIntgr.fr.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleFormsIntgr.ja-JP.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleFormsIntgr.ja.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleFormsIntgr.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleTaskManager.de-DE.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleTaskManager.de.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleTaskManager.en-US.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleTaskManager.en.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleTaskManager.fr-FR.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleTaskManager.fr.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleTaskManager.ja-JP.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleTaskManager.ja.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleTaskManager.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleWorkflow.de-DE.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleWorkflow.de.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleWorkflow.en-US.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleWorkflow.en.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleWorkflow.fr-FR.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleWorkflow.fr.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleWorkflow.ja-JP.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleWorkflow.ja.resx /F /Q
Del %WEBAPPDIR%\App_GlobalResources\AdobeLiveCycleWorkflow.resx /F /Q
```

```
popd
Echo Restarting IIS worker process
IISRESET
set _my_datetime=%date% %time%
@echo on
echo End Installation at %_my_datetime%
@echo off
cmd /k
```

2 Set values for the following variables:

**%STSADM%** The location of the STSADM utility that you defined as part of the web part installation.

**%TEMPLATEDIR%** The TEMPLATES directory on the SharePoint server.

**%SITEURL%** The URL of the site on which you want to disable the ADEP Document Services features.

3 Save the file as Uninstall-sharepoint-connector.bat in the location where you have extracted ADEP Document Services web part at the time of installation on the SharePoint server. This folder contains the install.bat file that you used to install the web part. and double-click to start uninstallation.

4 From Windows Explorer, double-click the uninstall-sharepoint-connector.bat file to start the uninstallation. The uninstallation process restarts the IIS Server.

5 After the uninstallation steps are completed, open the web.config file of your web application in a text editor.

6 Remove the elements <system.serviceModel> </system.serviceModel> from this file, and then save the file.